

PAT-NO: JP362132047A

DOCUMENT-IDENTIFIER: JP 62132047 A

TITLE: SHOCK DAMPING DEVICE FOR  
MOVER

PUBN-DATE: June 15, 1987

INVENTOR-INFORMATION:

NAME

ENOSAWA, KAZUO

FUKAZAWA, HIDEJI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

MATSUSHITA GRAPHIC COMMUN SYST INC

N/A

APPL-NO: JP60272730

APPL-DATE: December 4, 1985

INT-CL (IPC): F16F007/00

US-CL-CURRENT: 188/164, 267/136

ABSTRACT:

PURPOSE: To enhance durability with no generation of mechanical wear, by damping a shock between a mover and a fixed member through repulsive force generated between a permanent magnet and an electromagnet.

CONSTITUTION: A shock damping device is applied to a mover 6 which moves running on a fixed bed part 5a formed on a fixed member 5. If the mover 5 moves to the side of a position restricting part 5b along a guide shaft 11, the device, which actuates a control unit 9 by a detecting switch, excites an electromagnet 8. And if the mover 6 approaches the position restricting part 5b, the electromagnet 8 and a permanent magnet 12 come to repel each other. Here from the fact that repulsive force between each magnet 8, 12 is in inverse proportion to a square of distance, the device, in which the repulsive force

acceleratively increases as the mover 6 approaches the position restricting part 5b, decelerates the mover 6 to be stopped at an increasing temp.

COPYRIGHT: (C)1987,JPO&Japio